

EXIDE[®] BIKE

★★★★ FACTORY SEALED



★★ MAINTENANCE FREE



★ CONVENTIONAL New!



'Seal' or 'sealed', refers to leak-proof/spill-proof capability under normal operating. The release of minimal gas during recharge may occur, which is normal.

New! New 6-pack acid bottle included

MOTORCYCLE & SPORT BATTERIES

FACTORY SEALED ★★★★	MAINTENANCE FREE ★★	CONVENTIONAL <small>New!</small> ★	
<ul style="list-style-type: none"> • High power + Deep Discharge performances • Multi-positional fitment • Factory Seal guaranteed by manufacturer (VRLA Class) 	<ul style="list-style-type: none"> • High power performances • Multi-positional fitment • Fully sealed after plug installation 	<ul style="list-style-type: none"> • Standard performances • Upright Installation only • Not sealed (Regular gas emission) 	Features
<ul style="list-style-type: none"> • Unrestricted (cheaper) distribution • Acid already into cells (time and effort saving) • No acid handling at anytime (no environmental issues) • Special label indicates recharge when normal stocking period is exceeded • 16 types covering 40% of the Parc 	<ul style="list-style-type: none"> • Simple rules for distribution displayed on the packing • Including a 6-pack acid bottle for initial filling • Acid handling simplified (right amount) by the pack • Recharge during stocking period is not required • 27 types covering 50% of the Parc 	<ul style="list-style-type: none"> • Simple rules for distribution displayed on the packing • Including a 6-pack acid bottle for initial filling • Acid handling simplified (right amount) by the pack • Recharge during stocking period is not required • 68 types covering 60% of the Parc 	Distributor Benefits
<ul style="list-style-type: none"> • Assistance not required at all (no wait for installation) • Extended life • Suitable for cold weather or motion tilting • Absolutely Maintenance Free • Approved for Seasonal use • Handling precautions not required (leak-proof, spill-proof) 	<ul style="list-style-type: none"> • Requires assistance to put in service • Extended life • Suitable for cold weather or motion tilting • Absolutely Maintenance Free • Approved for Seasonal use • Handling precautions not required (leak-proof) 	<ul style="list-style-type: none"> • Requires assistance to put in service • Regular life duration • For use in regular conditions • Consumed water could require maintenance • Seasonal use could require maintenance • Handling precautions required to avoid acid spillage 	End-Users Benefits
<ul style="list-style-type: none"> • AGM-GEL construction (immobilised acid in cells) • Wet charged (with acid in cells) Ready for use • Calcium (Ca) alloy in plates • AGM (Glass mat) separator 	<ul style="list-style-type: none"> • AGM construction (immobilised acid in cells) • Dry charged (without acid in cells) 6-pack acid bottle included • Calcium (Ca) alloy in plates • AGM (Glass mat) separator 	<ul style="list-style-type: none"> • Lead acid construction (wet flooded) • Dry charged (without acid in cells) 6-pack acid bottle included • Antimony (Sb) alloy in plates • Glass fibre separators 	Characteristics

MAIN ADVANTAGES

	FACTORY SEALED ★★★★	MAINTENANCE FREE ★★★	CONVENTIONAL ★
Ready for installation and use	✓		
Factory seal guaranteed by manufacturer	✓	(1)	
Side mounting approved	✓	✓	
Acid bottle included for initial filling	(2)	✓	✓
Technology	AGM-GEL charged	AGM DRY	DRY
Electrical Performances	High Power Deep Discharge	High Power	Standard Power

(1) Becoming sealed after filling / (2) Not required as acid is already into the cells

RECOMMENDED APPLICATIONS

	FACTORY SEALED ★★★★	MAINTENANCE FREE ★★★	CONVENTIONAL ★
Motorcycles + Scooter	High class (3) + Off Road	Most Popular	Classic + Collection + Old park
All Terrain + Utility Vehicles			
Snow mobile			
Personal Watercraft + Jetski			
Tractor + Garden machines			

(3) BMW compliant

New! New 6-pack acid bottle included

12V FACTORY SEALED Battery Specifications

code	performances		dimensions			features			
	capacity 10h (Ah)	CCA/EN Reference (A)	L(mm)	W(mm)	H(mm)	Polarity	terminal type		
							front	side	top
AGM12-4	3	50	113	70	85	+	+	+	
AGM12-5	4	70	113	70	105	+	+	+	
AGM12-7F	7	85	150	65	100	+	+	+	
AGM12-8	8,6	145	150	87	93	+	+	+	
AGM12-9	9	120	135	75	139	+	+	+	
AGM12-10	10	150	150	87	130	+	+	+	
AGM12-12	12	200	150	87	145	+	+	+	
AGM12-12F	12	150	150	100	100	+	+	+	
GEL12-14	14 (20h)	150	150	87	145	+	+	+	
AGM12-14	12	210	134	89	164	+	+	+	
GEL12-16	16 (20h)	100	180	75	165	+	+	+	
AGM12-18	18	250	181	77	167	+	+	+	
GEL12-19	19 (20h)	170	185	80	170	+	+	+	
AGM12-23	21	350	205	86	162	+	+	+	
GEL12-30	30 (20h)	180	197	132	186	+	+	+	
AGM12-31	30	430	166	126	175	+	+	+	

12V MAINTENANCE FREE Battery Specifications

code	performances		dimensions			features			
	capacity 10h (Ah)	CCA/EN Reference (A)	L(mm)	W(mm)	H(mm)	Polarity	terminal type		
							front	side	top
YT4B-B5	2,3	35	113	38	85	+	+	+	
YTR4A-B5	2,3	35	113	48	85	+	+	+	
YTX4L-B5	3	50	113	70	85	+	+	+	
YTX5L-B5	4	70	113	70	105	+	+	+	
YTX7A-B5	6	90	150	87	93	+	+	+	
YTX7L-B5	6	100	113	70	130	+	+	+	
YT7-B5	6	100	113	70	105	+	+	+	
YT7B-B5	6,5	85	150	65	93	+	+	+	
YT9B-B5	8	110	150	70	105	+	+	+	
YTX9-B5	8	120	150	87	105	+	+	+	
YT210-B5	8,6	145	150	87	93	+	+	+	
YTX9C-B5	9	120	135	75	139	+	+	+	
YT12A-B5	9,5	130	150	87	105	+	+	+	
YT12B-B5	10	160	150	70	130	+	+	+	
YTX12-B5	10	150	150	87	130	+	+	+	
YT214-B5	11,2	205	150	87	110	+	+	+	
YT14B-B5	12	190	150	70	145	+	+	+	
YTX14-B5	12	200	150	87	145	+	+	+	
YTX14L-B5	12	200	150	87	145	+	+	+	
YTX14AH-B5	12	210	134	89	164	+	+	+	
YTX14AHL-B5	12	210	134	89	164	+	+	+	
YTX15L-B5	13	210	175	87	130	+	+	+	
YTX16-B5	14	215	150	87	161	+	+	+	
YTX20H-B5	18	270	175	87	155	+	+	+	
YTX20HL-B5	18	270	175	87	155	+	+	+	
YTX20CH-B5	18	230	150	87	161	+	+	+	
YTX24HL-B5	21	350	205	87	162	+	+	+	

6V CONVENTIONAL Battery Specifications

code	performances		dimensions			features			
	capacity 10h (Ah)	CCA/EN Reference (A)	L(mm)	W(mm)	H(mm)	Polarity	terminal type		
							front	side	top
6N4-2A	4	35	70	70	95	+	+	+	
6N4-2A-4	4	35	70	70	95	+	+	+	
6N4B-2A	4	35	101	47	95	+	+	+	
6N6-3B-1	6	40	98	56	110	+	+	+	
6A9-6	10	90	90	82	160	+	+	+	
6N11A-1B	11	95	121	59	131	+	+	+	
6N12A-2D	12	100	155	56	115	+	+	+	
B3B-6A	13	105	119	83	162	+	+	+	

12V CONVENTIONAL Battery Specifications **New!**

code	performances		dimensions			features			
	capacity 10h (Ah)	CCA/EN Reference (A)	L(mm)	W(mm)	H(mm)	Polarity	terminal type		
							front	side	top
YB2,5L-C	2,5	20	80	70	105	+	+	+	
YB3L-A	3	25	98	56	110	+	+	+	
YB3L-B	3	25	98	56	110	+	+	+	
YB4L-A	4	50	120	70	92	+	+	+	
YB4L-B	4	50	120	70	92	+	+	+	
12N5-3B	5	40	120	60	130	+	+	+	
YB5L-B	5	65	120	60	130	+	+	+	
12N5,5-3B	5,5	45	135	60	130	+	+	+	
12N5,5A-3B	5,5	40	103	90	114	+	+	+	
12N7-3B	7	75	135	75	133	+	+	+	
12N7-4B	7	75	135	75	133	+	+	+	
YB7C-A	8	90	130	90	114	+	+	+	
YB7-A	8	85	135	75	133	+	+	+	
YB7L-B	8	85	135	75	133	+	+	+	
12N9-3B	9	85	135	75	139	+	+	+	
12N9-4B-1	9	85	135	75	139	+	+	+	
YB9-B	9	100	135	75	139	+	+	+	
YB9L-A2	9	100	135	75	139	+	+	+	
YB9L-B	9	100	135	75	139	+	+	+	
12N10-3B	10	110	135	90	145	+	+	+	
YB10L-A2	11	130	135	90	145	+	+	+	
YB10L-B	11	130	135	90	145	+	+	+	
YB10L-B2	11	130	135	90	145	+	+	+	
12N12A-4A-1	12	115	134	80	160	+	+	+	
YB12A-A	12	165	134	80	160	+	+	+	
YB12A-B	12	165	134	80	160	+	+	+	
YB12AL-A	12	165	134	80	160	+	+	+	
YB12AL-A2	12	165	134	80	160	+	+	+	
YB12B-B2	12	120	160	90	130	+	+	+	
YB12C-A	12	165	134	80	175	+	+	+	
12N14-3A	14	130	134	89	166	+	+	+	
YB14-A2	14	145	134	89	166	+	+	+	
YB14-B2	14	145	134	89	166	+	+	+	
YB14L-A2	14	145	134	89	166	+	+	+	
YB14L-B2	14	145	134	89	166	+	+	+	
YB14A-A2	14	145	134	89	176	+	+	+	
HYB16A-A	16	150	149	89	178	+	+	+	
YB16AL-A2	16	175	205	70	162	+	+	+	
YB16B-A	16	175	160	90	162	+	+	+	
YB16B-A1	16	175	160	90	162	+	+	+	
12N18-3	18	165	205	90	162	+	+	+	
YB18L-A	18	190	180	90	162	+	+	+	
YB16-B	19	190	175	100	155	+	+	+	
YB16CL-B	19	190	175	100	175	+	+	+	
YB16L-B	19	190	175	100	155	+	+	+	
12Y16A-3A	20	210	185	81	170	+	+	+	
12Y16A-3B	20	210	185	81	170	+	+	+	
Y50-N18L-A	20	260	205	90	162	+	+	+	
Y50-N18L-A3	20	260	205	90	162	+	+	+	
12N24-3A	24	220	184	124	175	+	+	+	
12N24-4A	24	220	184	124	175	+	+	+	
U1-9	24	240	196	130	180	+	+	+	
Y60-N24-A	28	280	184	124	169	+	+	+	
Y60-N24AL-B	28	280	184	124	169	+	+	+	
Y60-N24L-A	28	280	184	124	169	+	+	+	
Y60-N30-A	30	300	185	128	168	+	+	+	
Y60-N30L-A	30	300	185	128	168	+	+	+	
Y60-N30L-B	30	300	185	128	168	+	+	+	
YB30L-B	30	300	165	130	176	+	+	+	
U1R-11	30	300	196	130	180	+	+	+	

New! New 6-pack acid bottle included

EXIDE[®] BIKE

MOTORCYCLE & SPORT BATTERIES

2012

